

PART NUMBER:

TYPE:  JOB NAME:



### ORDERING INFORMATION

#### 1 MODEL & SIZE

- Celia 24** 24" Diameter
- Celia 36** 36" Diameter
- Celia 48** 48" Diameter
- Celia 60** 60" Diameter
- Celia 72** 72" Diameter

#### 2 COLOR TEMP.

- 2700** 2700K
- 3000** 3000K
- 3500** 3500K
- 4000** 4000K

#### 3 COLOR RENDERING

- 80 CRI (Standard)
- 90** 90 CRI

#### 4 LUMEN OUTPUT

- 450** 450 Designed Lumens/ft
- 900** 900 Designed Lumens/ft
- CUS** Custom Output (consult factory)

#### 5 VOLTAGE

- UNV** 120-277V (0-10V Dimming)

#### 6 MOUNTING

- CPC/DM/09** 9" Canopy with Driver, Cables Pitched to Canopy
- CPC/RM/06** 6" Canopy with Remote Driver, Cables Pitched to Canopy
- VS/DM/09** 9" Canopy with Driver, Vertical Suspension
- VS/RM/06** 6" Canopy with Remote Driver, Vertical Suspension

#### 7 COLOR CODE

- BKG** Gloss Black
- BKS** Satin Black
- BRZ** Bronze
- WHG** Gloss White
- WHS** Satin White
- BLU** Blue
- GRN** Green
- GDS** Satin Gold
- CRD** Cardinal Red
- SLV** Silver
- RAL** RAL\_\_\_\_\_
- CUS** CUSTOM

### SPECIFICATIONS

<b>SIZES:</b>	2.75"H x 24-72" Diameter
<b>CONSTRUCTION:</b>	Rigid body construction to allow heat dissipation and prevent damaging and warping. Construction of the 24-60" rings are fabricated as non-modular single frame. Larger sizes are shipped modular
<b>DIFFUSERS:</b>	Precision cut acrylic lens eliminates any LED pixelation and provides smooth symmetric distribution.
<b>MOUNTING CONFIGURATIONS:</b>	Cables can be centered pitched to canopy (CPC) or vertically suspended (VS). Sizes above 48" require (VS) option.
<b>SUPPORTS:</b>	All fixtures supplied standard with 8 feet stainless steel cables. Additional cable lengths available on request. <i>Adequate ceiling support required at aircraft cable mounting points. Request installation guide specific to the size and illumination for each fixture upon ordering to identify mounting support points.</i>
<b>DRIVERS:</b>	LED drivers are 120-277V and 0-10V dimming. Drivers are directed mounted in the canopy or optional remote mounted (RM) driver in enclosure.
<b>LED:</b>	LED's are mounted to metal surface to maximize heat dissipation. Available in 2700, 3000, 3500 or 4000K. Standard 80CRI, 90CRI optional.
<b>ILLUMINATION:</b>	Available in 450 or 900 designed lumens/ft. Output can be customized by consulting factory.
<b>FINISHES:</b>	Powder coated finish applied to housing and canopies. Available in a variety of powder coated finishes.
<b>FABRICATION:</b>	Fabricated and assembled in the US.
<b>LISTINGS:</b>	UL listed for dry or damp indoor locations.
<b>WARRANTY:</b>	5 year limited warranty on LED and electronic parts. Consult terms and conditions for full details.

### RENDERINGS AND DIMENSIONS

