

PART NUMBER:

TYPE:

JOB NAME:



ORDERING INFORMATION

1 MODEL & SIZE

- Jan-R 24** 24" Diameter
- Jan-R 36** 36" Diameter
- Jan-R 48** 48" Diameter
- Jan-R 60** 60" Diameter
- Jan-R 72** 72" Diameter

2 COLOR TEMP.

- 2700** 2700K
- 3000** 3000K
- 3500** 3500K
- 4000** 4000K

3 COLOR RENDERING

- 80 CRI (Standard)
- 90** 90 CRI

4 LUMEN OUTPUT

- 450** 450 Designed Lumens/ft
- 900** 900 Designed Lumens/ft
- CUS** Custom Output (consult factory)

5 VOLTAGE

- UNV** 120-277V (0-10V Dimming)

6 MOUNTING

- CPC/DM/09** 9" Canopy with Driver, Cables Pitched to Canopy
- CPC/RM/06** 6" Canopy with Remote Driver, Cables Pitched to Canopy
- VS/DM/09** 9" Canopy with Driver, Vertical Suspension
- VS/RM/06** 6" Canopy with Remote Driver, Vertical Suspension

7 COLOR CODE

- BKG** Gloss Black
- BKS** Satin Black
- BRZ** Bronze
- WHG** Gloss White
- WHS** Satin White
- BLU** Blue
- GRN** Green
- GDS** Satin Gold
- CRD** Cardinal Red
- SLV** Silver
- RAL** RAL_____
- CUS** CUSTOM

SPECIFICATIONS

| | |
|---------------------------------|--|
| SIZES: | 2.75"H x 24-72" Diameter |
| CONSTRUCTION: | Rigid body construction to allow heat dissipation and prevent damaging and warping. Construction of the 24-60" rings are fabricated as non-modular single frame. Larger sizes are shipped modular |
| DIFFUSERS: | Precision cut acrylic lens eliminates any LED pixelation and provides smooth symmetric distribution. |
| MOUNTING CONFIGURATIONS: | Cables can be centered pitched to canopy (CPC) or vertically suspended (VS). Sizes above 48" require (VS) option. |
| SUPPORTS: | All fixtures supplied standard with 8 feet stainless steel cables. Additional cable lengths available on request. <i>Adequate ceiling support required at aircraft cable mounting points. Request installation guide specific to the size and illumination for each fixture upon ordering to identify mounting support points.</i> |
| DRIVERS: | LED drivers are 120-277V and 0-10V dimming. Drivers are directed mounted in the canopy or optional remote mounted (RM) driver in enclosure. |
| LED: | LED's are mounted to metal surface to maximize heat dissipation. Available in 2700, 3000, 3500 or 4000K. Standard 80CRI, 90CRI optional. |
| ILLUMINATION: | Available in 450 or 900 designed lumens/ft. Output can be customized by consulting factory. |
| FINISHES: | Powder coated finish applied to housing and canopies. Available in a variety of powder coated finishes. |
| FABRICATION: | Fabricated and assembled in the US. |
| LISTINGS: | UL listed for dry or damp indoor locations. |
| WARRANTY: | 5 year limited warranty on LED and electronic parts. Consult terms and conditions for full details. |

RENDERINGS AND DIMENSIONS

