

GEO-TGEO Triangle

TYPE:	JOB NAME
ORDERING INF	ORMATION
1 MODEL & SIZE	2 COLO
☐ GEO-T 24 24 ☐ GEO-T 48 48	_ 0000 0
3 COLOR RENDERING	G 4 LUME
80 80 CRI (Stan-dard)90 90 CRI	☐ 490 49 ☐ 900 90 ☐ CUS Cu

PART NUMBER:

TYPE:		JOB NAME:
ORDERING	G INFORM <i>i</i>	ATION
1 MODEL &	SIZE	2 COLOR TEMP.
☐ GEO-T 24 ☐ GEO-T 48	24" 48"	3000 3000К3500 3500К4000 4000К
COLOR REN	DERING	4 LUMEN OUTPUT
□ 80 80 CRI (Sta	an-dard)	 490 490 Designed Lumens/ft 900 900 Designed Lumens/ft CUS Custom Output (consult factory
VOLTAGE UNV 120-277	V (0-10V Dimming)	
6 MOUNTING	<u>.</u>	
VS/DM/08 8" CPC/RM/08 6	Canopy with Driver	er, Cables pitched to Canopy r, Vertical Suspension to Ceiling note Driver, Cables pitched to Canopy ote Driver, Vertical Suspension to Ceiling
7 COLOR CO		
BKG Gloss Black BKS Satin Black BRZ Bronze		
WHG Gloss W WHS Satin W		
GRN Green		
GDS Satin Go CRD Cardinal SLV Silver	Red	
CUS CUSTOM		



GEO-TGEO Triangle

SPECIFICATIONS

SIZES: Available in 24" or 48" triangle

CONSTRUCTION: Rigid body construction to allow heat dissipation

and prevent damaging and warping. Construction of the rectangles are fabricated as non-modular single

frames.

DIFFUSERS: Precision cut acrylic lens eliminates any LED

pixelation and provides smooth symmetric distribution. Standard configuration is provided with 3 griplock cables and cord that mount to

canopy.

SUPPORTS: All fixtures supplied standard with 8 feet

stainless steel cables. Additional cable lengths

available on request.

DRIVERS: LED drivers are 120-277V and 0-10V dimming. Drivers

are directed mounted in the canopy or optional remote mounted (RM) driver in enclosure.

LED: LED's are mounted to metal surface to maximize

heat dissipation. Available in 3000, 3500 or 4000K. Standard 80CRI, 90CRI optional.

ILLUMINATION: Available in 490 or 900 designed lumens/ft. Output

can be customized by consulting factory.

FINISHES: Powder coated finish applied to housing and

canopies. Available in a variety of powder coated

finishes.

FABRICATION: Fabricated and assembled in the US.

LISTINGS: UL listed for dry or damp indoor locations.

WARRANTY: 5 year limited warranty on LED and electronic

parts. Consult terms and conditions for full details.

RENDERINGS AND DIMENSIONS



