

Illusions School House



| | PART NUMBER: | | | | | | |
|---|--|-----------------------------------|---|--|--|---|--|
| | | TYPE: | | | JOB NAM | 1E: | |
| | | | | | | | |
| ORDERING INFORMATION | | | | | | | |
| | | | | | | | |
| 0 | MOD | EL* & SIZE | | | 2 COLOR TEMP. | | |
| | IL-SHA IL-SHB IL-SHC IL-SHD | 12 3/4" Diameter 15 1/4" Diameter | | | 3000 3000к3500 3500к4000 4000к | | |
| 2 | CRI | RI | | | 4 WATTAGE | | |
| | 80 80 0 (Standa 90 | | | | □ 8□ 12□ 16□ 20 | 8 Watts 12 Watts 16 Watts 20 Watts | |
| VOLTAGE UNV 120-277V (0-10V Dimming) MOUNTING OPTIONS | | | | | | | |
| STM/DM/08 8" Canopy with Driver, Stem mounted STM/DM/06 6" Canopy with Remote Driver, Stem mounted | | | | | | | |
| 7 COLOR CODE | | | | | | | |
| | BKG BKS | Gloss Black Satin Black | | | | | |
| | BRZ WHG | Bronze Gloss White | | | | | |
| | WHS | Satin White | | | | | |
| | BLU | Blue | | | | | |
| | GRN | Green | | | | | |
| | GDS CRD | Satin Gold Cardinal Red | I | | | | |
| | SLV RAL CUS | Silver RAL CUSTOM | | | | | |



Illusions School House

SPECIFICATIONS

SIZES: IL-SH-A: 9 3/8" H x 11 3/4" H

IL-SH-B: 9 3/8" H x 13 1/4" W IL-SH-C: 9 3/8" W x 15 1/4" W IL-SH-D: 9 3/8" H x 17 1/2" W

CONSTRUCTION: Acrlic globe mounted to rigid metal cover and

suspended to Canopy. LED driver is mounted in canopy or can be remote mounted in enclosure. Cover, stem and canopy finished in durable powder coated finish.

DIFFUSERS: Precision cut acrylic lens eliminates any LED pixelation a

provides smooth symmetric distribution.

MOUNTING Standard configuration is provided with (3)12" sections

CONFIGURATIONS: and (1) 8" section. For longer lengths or dedicated stem

lengths, please consult factory.

DRIVERS: LED drivers are 120-277V and 0-10V dimming. Drivers ar

direct mounted in the canopy or optional remote

mounted (RM) driver in enclosure.

LED's are mounted to metal surface to maximize heat

dissipation. Available in 3000, 3500 or 4000K.

Standard 80CRI, 90CRI optional.

ILLUMINATION: SH-A globe: 1,074 lumens at 8W

SH-B globe: 1,463 lumens at 12W SH-C globe: 1,987 lumens at 16W SH-D globe: 2,687 lumens at 20W

For other outputs and configurations, please consult factory

FINISHES: Powder coated finish applied to housing and canopies.

Available in a variety of powder coated finishes.

FABRICATION: Fabricated and assembled in the US.

LISTINGS: UL listed for dry or damp indoor locations.

WARRANTY: 5 year limited warranty on LED and electronic parts.


Consult terms and conditions for full details.

RENDERINGS AND DIMENSIONS

Available Sizes:




9 3/8" x 11 3/4"



9.3/8" x 15.1/4"

9 3/8" x 13 1/4"

18" x 24"



17 1/2*