



PART NUMBER: TYPE: JOB NAME: ORDERING INFORMATION 1 MODEL* & SIZE 2 COLOR TEMP. FRAME-0622 26" Length **3000** 3000K FRAME-0644 48" Length **3500** 3500K **4000** 4000K FRAME-0658 62" Length 4 WATTAGE 3 CRI **80** 80 CRI (Standard) 18 18 Watts 32 32 Watts 90 42 42 Watts 5 VOLTAGE **UNV** 120-277V (0-10V Dimming)

6 MOUNTING OPTIONS

- STM/DM/08 8" Canopy with Driver, stem mounted
- CBL/DM/08 8" Canopy with Driver, Cable mounted
- STM/RM/06 6" Canopy with Remote Driver, stem mounted
- CBL/DM/06 6" Canopy with Remote Driver, Cable mounted

7 COLOR CODE

BKG	Gloss Black
BKS	Satin Black
BRZ	Bronze
WHG	Gloss White
WHS	Satin White
BLU	Blue
GRN	Green
GDS	Satin Gold
CRD	Cardinal Red
SLV	Silver
RAL	RAL
CUS	CUSTOM

Frame



Frame

SPECIFICATIONS

SIZES:	6" Wide. 25, 47 and 62" lengths
CONSTRUCTION:	Acrlic tube mounted to rigid metal cover and suspended to Canopy. LED driver is mounted in canopy or can be remote mounted in enclosure. Optional bottom cap available. Cover and canopy finished in durable powder coated finish.
DIFFUSERS:	Precision cut acrylic lens eliminates any LED pixelation and provides smooth symmetric distribution.
MOUNTING CONFIGURATIONS:	Optional configurations can be provided with a 36" stem or (1) 96' griplock cable and power cable to mount to canopy. For longer lengths, please consult factory.
DRIVERS:	LED drivers are 120-277V and 0-10V dimming. Drivers are direct mounted in the canopy or optional remote mounted (RM) driver in enclosure.
LED:	LED's are mounted to metal surface to maximize heat dissipation. Available in 3000, 3500 or 4000K. Standard 80CRI, 90CRI optional.
ILLUMINATION:	 26": 1,917 lumens at 18W 48": 3,374 lumens at 32W 62": 4,575 lumens at 42W For other outputs and configurations, please consult factory
FINISHES:	Powder coated finish applied to housing and canopies. Available in a variety of powder coated finishes.
FABRICATION:	Fabricated and assembled in the US.
LISTINGS:	UL listed for dry or damp indoor locations.
WARRANTY:	5 year limited warranty on LED and electronic parts.

Consult terms and conditions for full details.

RENDERINGS AND DIMENSIONS

