



TYPE:	JOB NAME:
ORDERING INFORM	ATION
1 MODEL & SIZE	2 COLOR TEMP.
☐ GEO-SQ 26 26"	3000 3000К
☐ GEO-SQ 36 36"	3500 3500К
☐ GEO-SQ 48 48"	4000 4000K
☐ GEO-SQ 62 62"	
3 COLOR RENDERING	4 LUMEN OUTPUT
80 80 CRI (Stan-dard)	450 450 Designed Lumens/ft
90 90 CRI	900 900 Designed Lumens/ft
	CUS Custom Output (consult factory

5 VOLTAGE

6 MOUNTING

COLOR CODE

BKG Gloss BlackBKS Satin BlackBRZ BronzeWHG Gloss WhiteWHS Satin White

BLU BlueGRN GreenGDS Satin GoldCRD Cardinal Red

SLVSilver
RAL RAL
CUS CUSTOM

UNV 120-277V (0-10V Dimming)

CPC/DM/08 8" Canopy with Driver, Cables pitched to Canopy
 VS/DM/08 8" Canopy with Driver, Vertical Suspension to Ceiling
 CPC/RM/08 6" Canopy with Remote Driver, Cables pitched to Canopy
 VS/DM/06 6" Canopy with Remote Driver, Vertical Suspension to Ceiling

PART NUMBER:



GEO-SQGEO Square

SPECIFICATIONS

SIZES: Available in 26.5. 48.5 and 62.5" square shapes. Consult

factory for other sizes and options

CONSTRUCTION: Rigid body construction to allow heat dissipation

and prevent damaging and warping. Construction of the rectangles are fabricated as non-modular single

frames.

DIFFUSERS: Precision cut acrylic lens eliminates any LED

pixelation and provides smooth symmetric distribution. Standard configuration is provided with griplock cables and cord that mount to

canopy.

SUPPORTS: All fixtures supplied standard with 8 feet

stainless steel cables. Additional cable lengths

available on request.

DRIVERS: LED drivers are 120-277V and 0-10V dimming. Drivers

are directed mounted in the canopy or optional remote mounted (RM) driver in enclosure.

LED: LED's are mounted to metal surface to maximize

heat dissipation. Available in 3000, 3500 or 4000K. Standard 80CRI, 90CRI optional.

ILLUMINATION: Available in 490 or 900 designed lumens/ft. Output

can be customized by consulting factory.

FINISHES: Powder coated finish applied to housing and

canopies. Available in a variety of powder coated

finishes.


FABRICATION: Fabricated and assembled in the US.

LISTINGS: UL listed for dry or damp indoor locations.


WARRANTY: 5 year limited warranty on LED and electronic

parts. Consult terms and conditions for full details.

RENDERINGS AND DIMENSIONS



SIDE MOUNT CONFIGURATION



TOP MOUNTED CONFIGURATION