

## Elation Carmel

PART NUMBER:		
TYPE:	JOB NAME:	



	ITPE:	JOB NAIVIE:
ORDE	RING INFORMATION	ON
☐ ELA/C	DEL* & SIZE ML 30 30" Diameter ML 45 45" Diameter	2 COLOR TEMP.  □ 3000 3000К □ 3500 3500К
	ML 60 60" Diameter	<b>4000</b> 4000к
3 CRI		4 WATTAGE
80 80 0		<b>36</b> 36 Watts
(Standa <b>90</b>	ard)	<b>56</b> 56 Watts
		<b>63</b> 63 Watts
<ul> <li>VOLTAGE         <ul> <li>UNV 120-277V (0-10V Dimming)</li> </ul> </li> <li>MOUNTING OPTIONS         <ul> <li>CPC/DM/08 8" Canopy with Driver, Stem &amp; Cable mounted to center canopy</li> <li>CPC/RM/08 8" Canopy with Remote Driver, Stem &amp; Cable mounted to center canopy</li> </ul> </li> <li>COLOR CODE</li> </ul>		
BKG	Gloss Black	
BKS	Satin Black	
☐ BRZ	Bronze Gloss White	
WHS	Satin White	
BLU	Blue	
GRN	Green	
GDS	Satin Gold	
CRD	Cardinal Red	
SLV	Silver	
RAL	RAL	
CUS	CUSTOM	



## **Elation Carmel**

## **SPECIFICATIONS**

30"W x 10"H SIZES:

45"W x 10"H 60"W x 10"H

Acrylic disc mounted to rigid cover and suspended to **CONSTRUCTION:** 

Canopy. LED driver is mounted in canopy or can be remote mounted in enclosure. Covers, stem and canopy

finished in durable powder coated finish.

Precision formed acrylic dome eliminates any LED **DIFFUSERS:** 

> pixelation and provides smooth symmetric distribution. Optional perimeter acrylic colors are available. Please

consult factory for options.

MOUNTING

Standard configurations are provided with (4) griplock cables and stems that mount to the Center Canopy. **CONFIGURATIONS:** 

Standard cables are 96" in length. For longer lengths,

please consult factory.

LED drivers are 120-277V and 0-10V dimming. Drivers are **DRIVERS:** 

direct mounted in the canopy or optional remote

mounted (RM) driver in enclosure.

LED's are mounted to metal surface to maximize heat LED:

dissipation. Available in 3000, 3500 or 4000K.

Standard 80CRI, 90CRI optional.

30" Elation: 2,770 lumens at 36W **ILLUMINATION:** 

45" Elation: 4.717 lumens at 56W 60" Elation: 5,571 lumens at 63W

For other outputs and configurations, please consult factory

Powder coated finish applied to housing and canopies. **FINISHES:** 

Available in a variety of powder coated finishes.

Fabricated and assembled in the US. **FABRICATION:** 

UL listed for dry or damp indoor locations. LISTINGS:

5 year limited warranty on LED and electronic parts. **WARRANTY:** 

Consult terms and conditions for full details.

## **RENDERINGS AND DIMENSIONS**



