



•	

	PA	PART NUMBER:							
	TY	/PE:			JOB	NAM	1E:		
					· ·				
O	ORDERING INFORMATION								
1	MODE	L* &	SIZE		20	OLO	OR TEMP.		
	VODA 23		23" Dian	neter	3 0	000	3000K		
	VODA 34		34" Diam	eter	□ 3!	500	3500K		
					40	000	4000K		
			a						
2	MODE	L* &	SIZE		4 W	/AI	TAGE		
	80 80 CR (Stan-dar				_ 23	3	23 Watts		
	90	u)			<u> </u>	3	53 Watts		
5	VOLTA	GE							
			(0-10V [Dimming)					
				37					
6	MOUN	ITING	OPTIC	ONS					
	CPC/DM	/08 8″	Canopy	with Driver, C	Cable Pitch	ed f	rom Canopy		
	CPC/RM	CPC/RM/06 6" Canopy with Remote Driver, Cable Pitched from Canopy							
		STM/DM/08 8" Canopy with Driver, Stem mounted							
	STM/DM	/06 6"	Canopy	with Remote	Driver, Ste	em r	mounted		
	501.5 =		_						
	COLOR	COE)Ē						
	BKG G	aloss E	lack						
	BKS S	atin B	lack						
	WHG Glo	ss Wh	ite						

WHS Satin White

BRZ

SLV RAL

CUS

Bronze

Silver

RAL____CUSTOM





SPECIFICATIONS

SIZES: 22.5" or 34" diameters.

CONSTRUCTION: Rigid ring body construction to allow heat

dissipation and prevent damaging and warping. Construction of the 24" rings to 60" rings are fabricated as non-modular single frame rings.

DIFFUSERS: Precision cut acrylic lens eliminates any LED

pixelation and provides smooth symmetric

distribution.

MOUNTING Standard configuration is provided with 3 griplock

CONFIGURATIONS: cables and cord that mount to canopy. Stem mount option available and is provided with (3)12"

sections and (1) 8" section.

SUPPORTS: All fixtures supplied standard with 8 feet

stainless steel cables. Additional cable lengths

available on request.

DRIVERS: LED drivers are 120-277V and 0-10V dimming. Drivers

are directed mounted in the canopy or optional remote mounted (RM) driver in enclosure.

LED: LED's are mounted to metal surface to maximize

heat dissipation. Available in 3000, 3500 or 4000K. Standard 80CRI, 90CRI optional.

ILLUMINATION: L22.5" delivers 2154 lumens at 23 watts. 34"

delivers 4965 lumens at 53 watts.

FINISHES: Powder coated finish applied to housing and

canopies. Available in a variety of powder coated

finishes.

FABRICATION: Fabricated and assembled in the US.

LISTINGS: UL listed for dry or damp indoor locations.

WARRANTY: 5 year limited warranty on LED and electronic

parts. Consult terms and conditions for full details.

RENDERINGS AND DIMENSIONS



